


# PowerLux® iCylinder™ Induction Luminaire



55W Induction 100-120V, 200-277V

## FIXTURE DIMENSIONS



## IES FILE PHOTOMETRIC DATA

Available upon request

## PACKING DATA

Carton size: 9"x9"x11" Weight: 8 lbs

## ORDERING INFORMATION

Model No.	Wattage	Lamp Kelvin (S/P Ratio)	Voltage	Color	Dimming
PC	55	830 (1.35)	100-120V	WH white	DM(2-level)
		840 (1.62)	200-277V	BN brown	
		850 (1.96)			

Part Number Example: PC55/840/277/WH

Description: PowerLux iCylinder Induction Luminaire 55W 4000K 200-277V White

Catalog#		Type
Project		
Note		Date
Prepared by		

## PROVEN QL INDUCTION LIGHTING TECHNOLOGY WORLDWIDE SINCE 1992

### APPLICATIONS

- For stairwell, lecture hall, airport lounge, entrance lobby and hard to reach locations

### SPECIFICATION FEATURES

- Up to 100,000 Hours rated lamp life
- Instant ON and instant re-strike
- CRI >80 White light no color shift
- Thermally engineered for sustainable operation designed according to local temperatures
- Pressed steel housing powder coated with white or brown paint finish
- Smooth/even beam pattern
- Specular aluminum reflector designed for maximum photometric efficiency and optimum light distribution
- Perfect replacement for HPS and MH HID light sources
- Overall weight is reduced for easy installation and maintenance
- Manufactured in the U.S.A.
- 2-level dimming ballast 50% power reducer to save energy during inactive times. Works with 0-10V control (Special Order Only)

## PowerLux® Corporation

US Manufacturer of Sustainable Energy Efficient Lighting Products  
Induction Lighting Proven Success Since 1999

1260 Liberty Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766  
Website: www.powerlux.com E-mail: klpowerlux@gmail.com

**PowerLux® Products Have Stood the Test of Time!**