


# PowerLux® iKobra™

## Dimmable Induction Luminaire with Bi-Level Motion Sensor and Photocell



55W Induction 100-120V, 200-277V  
85W Induction 100-120V, 200-277V  
165W Induction 100-120V, 200-277V

### FIXTURE DIMENSIONS



### IES FILE PHOTOMETRIC DATA

Available upon request

### PACKING DATA

Carton size: 30"x15"x9" Weight: 24 lbs (165W); 22 lbs (85W); 21 lbs (55W)  
Net Weight: 21 lbs (165W); 19 lbs (85W); 18 lbs (55W)

### ORDERING INFORMATION

Model No.	Wattage	Lamp Kelvin	Voltage
PKD	55	830	100-120V
	85	840	200-277V
	165	850	

Part Number Example: PKD85/840/120/DMSP

Description: PowerLux iKobra Dimmable Induction Luminaire 85W 4000K 100-120V with Bi-Level Motion Sensor and Photocell

Catalog#		Type
Project		
Note		Date
Prepared by		

**PROVEN QL INDUCTION LIGHTING TECHNOLOGY  
WORLDWIDE SINCE 1992**

### APPLICATIONS

- For street and parking lot lighting

### SPECIFICATION FEATURES

- Proven 100,000 hours rated lamp life
- Instant ON and instant re-strike with back-to-full brightness feature
- CRI >80 White light no color shift, no flickering
- Power factor >.90
- 2-level dimming ballast 50% power reducer to save energy during inactive times. Works with 0-10V control
- California Title 24 Compliant outdoor programmable motion sensor with photocell (see **PowerLux®** Dimmable Outdoor Motion Sensor with Photocell Brochure for details)
- Thermally engineered for sustainable operation designed according to local temperatures
- Die-cast aluminum housing powder coated gray paint finish
- Safety tempered glass lens
- Silicon rubber gasket
- Aluminum reflector designed for maximum photometric efficiency and optimum light distribution
- Cut-off distribution complies with Dark Sky compliance
- EPA-Effective Projected Area: 0.07 m<sup>2</sup>
- 2-inch pipe mounting 4 bolt slipfitter
- Overall weight is reduced for easy installation and maintenance
- Manufactured in the U.S.A.

## PowerLux® Corporation

**U.S. Manufacturer of Sustainable Energy Efficient Lighting Products**

**Induction Lighting Proven Success Since 1999**

1260 Liberty Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766

Website: [www.powerlux.com](http://www.powerlux.com) E-mail: [klpowerlux@gmail.com](mailto:klpowerlux@gmail.com)

**PowerLux® Products Have Stood the Test of Time!**

130613  
Patents pending  
Specifications subject to change without prior notice  
© 2010 by PowerLux® Corporation. All rights reserved