


PowerLux® LED Linda™ Custom Retrofit Kit



| | | |
|-------------|--|------|
| Catalog# | | Type |
| Project | | |
| Note | | Date |
| Prepared by | | |

LINDA™ DIMENSIONS



IES FILE PHOTOMETRIC DATA

Available on request

PACKING DATA

26x18"x18" Weight 13 lbs.

APPLICATIONS

- For use with existing Post Top Luminaire (use in parks, along walkways, roadways and areas where a distinctive nostalgic theme is prevalent).

SPECIFICATION FEATURES

- **PowerLux®** Linda™ features a traditional turn of the century shape
- Available in acrylic or polycarbonate
- Type V distribution, optimized for efficient light performance
- Improves downlight efficiency and eliminates uplight pollution
- Dome reflector available to comply with Dark Sky
- Designed for pole height between 10 and 20 feet
- Overall weight is reduced for easy installation and maintenance
- Decorative black plastic finial
- 5-year limited warranty
- Made in the U.S.A.
- UL Listed

LED SYSTEM FEATURES

- Thermally designed for 50,000 hours operation
- Typical downward lumen: see chart below
- Comfortable superior quality LED light
- Instant ON and instant re-strike with back-to-full brightness feature
- CCT available in 2700K, 3000K, 3500K or 4000K
- CRI > 80
- Universal voltage 120-240V or 120V-277V
- 2-level dimmable driver up to 80% power reducer to save energy during inactive times. Works with 0-10V control and sensor system.
- 5-year system warranty

Custom LED lumen packages available. Wattage varies according to lumen package.

ORDERING INFORMATION and SELECTION

| Model No. | Family Series | CCT 2700K | CCT 4000K | Voltage | Base | Refractor | Refractor | Reflector |
|-----------|---------------|---------------|---------------|---------|------|-------------------|-----------|-----------|
| PLEDMR | 2500 | 25W* / 2100lm | 25W* / 2350lm | 120-240 | 8" | Polycarbonate (P) | Clear (C) | Dome (D) |
| | 4000 | 34W* / 2700lm | 34W* / 3000lm | 120-277 | 9" | Acrylic (A) | White (W) | |
| | 6000 | 58W* / 4800lm | 59W* / 5100lm | | | | | |

*System wattage. System = driver + module

Part Number Example: PLEDMR/6000/827/120-240/9/PC

Description: PowerLux LED Linda Custom Retrofit 58W 2700K, 120-240V, 9" Polycarbonate Clear Refractor, Black Finial



PowerLux® Corporation

U.S. Manufacturer of Sustainable Energy Efficient Lighting Products

1260 Liberty Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766

Website: www.powerlux.com E-mail: klpowerlux@gmail.com

Based on prevailing model. Efficiency of ballast and efficacy of LED modules are ever improving. Please contact PowerLux.com for latest updated information.

PowerLux® Products Have Stood the Test of Time!

140325
Patents pending
Specifications subject to change without prior notice
© 2010 by PowerLux® Corporation. All rights reserved