

# PowerLux® LED Michele™ Custom Retrofit Kit



Catalog#		Type
Project		
Note		Date
Prepared by		

## APPLICATIONS

- For use with existing Post Top Luminaire. Use in parks, along walkways, roadways and areas where a distinctive nostalgic theme is prevalent.

## SPECIFICATION FEATURES


- **PowerLux® Michele™** features a traditional turn of the century shape
- Available in acrylic or polycarbonate
- Type V distribution, optimized for efficient light performance
- Improves downlight efficiency and eliminates uplight pollution
- Dome reflector available to comply with Dark Sky
- Designed for pole height between 10 and 20 feet
- Overall weight is reduced for easy installation and maintenance
- Decorative black plastic finial
- 5-year limited warranty
- Made in the U.S.A.
- UL Listed

## LED SYSTEM FEATURES

- Thermally designed for 50,000 hours operation
- Typical downward lumen: see chart below
- Comfortable superior quality LED light
- Instant ON and instant re-strike with back-to-full brightness feature
- CCT available in 2700K, 3000K, 3500K or 4000K
- CRI > 80
- Universal voltage 120-240V or 120V-277V
- 2-level dimmable driver up to 80% power reducer to save energy during inactive times. Works with 0-10V control and sensor system.
- 5-year system warranty

Custom LED lumen packages available. Wattage varies according to lumen package.

## MICHELE DIMENSIONS



## IES FILE PHOTOMETRIC DATA

Available on request

## PACKING DATA

19"x19"x28" Weight 12 lbs.

## ORDERING INFORMATION and SELECTION

Model No.	Family Series	CCT 2700K	CCT 4000K	Voltage	Base	Refractor	Refractor	Reflector
PLEDMR	2500	25W* / 2100lm	25W* / 2350lm	120-240	8"	Polycarbonate (P)	Clear (C)	Dome (D)
	4000	34W* / 2700lm	34W* / 3000lm	120-277	9"	Acrylic (A)	White (W)	
	6000	58W* / 4800lm	59W* / 5100lm					

\*System wattage. System = driver + module

Part Number Example: PLEDMR/4000/835/120-277/9/PC

Description: PowerLux LED Michele Custom Retrofit 34W 3500K, 120-277V, 9" Polycarbonate Clear Refractor, Black Finial



## PowerLux® Corporation

### U.S. Manufacturer of Sustainable Energy Efficient Lighting Products

1260 Liberty Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766

Website: [www.powerlux.com](http://www.powerlux.com) E-mail: [klpowerlux@gmail.com](mailto:klpowerlux@gmail.com)

Based on prevailing model. Efficiency of ballast and efficacy of LED modules are ever improving. Please contact [PowerLux](http://www.powerlux.com) for latest updated information.

**PowerLux® Products Have Stood the Test of Time!**

140318  
Patents pending  
Specifications subject to change without prior notice  
© 2010 by PowerLux® Corporation. All rights reserved