

PowerLux® LED Luminaire Post-Top Series



Shown with H1 and Dora globe



Catalog#		Type
Project		
Note		Date
Prepared by		


APPLICATIONS

- For use in parks, along walkways, roadways and areas where a distinctive nostalgic theme is prevalent.

SPECIFICATION FEATURES

- PowerLux® LED Luminaire Post-Top Series, with Dora Globe**, features a traditional turn of the century shape
- Available in acrylic or polycarbonate
- Type III or V distribution, optimized for efficient light performance
- Improves downlight efficiency and eliminates uplight pollution
- Sand cast aluminum housing available in H1 or H2 (H2 is hinged)
- Fits 3" Tenon (adaptor available for other diameter poles)
- Designed for pole height between 10 and 20 feet
- Overall weight is reduced for easy installation and maintenance
- Aluminum black finial available in style F1 or F2
- 5-year limited warranty
- Made in the U.S.A.

DIMENSIONS WITH THE DORA GLOBE



LED SYSTEM FEATURES

- Thermally designed for 50,000 hours operation
- Typical downward lumen: see chart below
- Comfortable superior quality LED light
- Instant ON and instant re-strike with back-to-full brightness feature
- LED module efficacy up to 130lm
- CCT available in 2700K, 3000K, 3500K or 4000K
- CRI > 80
- Universal voltage 120-240V or 120V-277V
- 2-level dimmable driver up to 80% power reducer to save energy during inactive times. Works with 0-10V control and sensor system.
- 5-year system warranty



Custom LED lumen packages available. Wattage varies according to lumen package.

PACKING DATA

Globe: 26"x18"x18" Weight 15 lbs
Housing: 15"x15"x 20" Weight 14 lbs

ORDERING INFORMATION and SELECTION

Model No.	Family Series	CCT 4000K	Voltage	Distribution	Dora Globe	Housing	Finial
PLEDPT	2500	25W* / 2350lm	120-240	III (3)	Polycarbonate (P)	H1	F1
	4000	34W* / 3000lm	120-277	V (5)	Acrylic (A)	H2	F2
	6000	59W* / 5100lm					

*System wattage. System = driver + LED module



F1 F2

Part Number Example: PLEDPT/6000/840/120240/3/DP/H2/F2

Description: PowerLux LED Luminaire Post-Top Series 59W 4000K, 120-240V, Type 3 Dora Polycarbonate Globe and Finial

PowerLux® Corporation

U.S. Manufacturer of Sustainable Energy Efficient Lighting Products

15000 y Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766

Website: www.powerlux.com E-mail: klpowerlux@gmail.com

Based on prevailing model. Efficiency of ballast and efficacy of LED modules are ever improving. Please contact [PowerLux®](http://www.powerlux.com) for latest updated information.

PowerLux® Products Have Stood the Test of Time!