


# PowerLux® Corporation

## Small Full Cutoff Wall Pack LED Luminaire




### FIXTURE DIMENSIONS:




### PHOTOMETRIC DATA

#### C Optics



Distance In Units Of Mounting Height  
Values Based On 10 Foot Mounting Height  
1/2 Maximum Candela Trace Shown As Dashed Curve  
(\*) = Maximum Candela Point

#### F Optics



Distance In Units Of Mounting Height  
Values Based On 10 Foot Mounting Height  
1/2 Maximum Candela Trace Shown As Dashed Curve  
(\*) = Maximum Candela Point

### ORDERING INFORMATION

Model No.	Wattage	CCT	Optics	Lens	Input Voltage	Additional Options
PLEDSFCWP	22W	5000K	C=Type 3 F=Medium Beam Spread	G=Clear Glass P=Clear Prismatic Glass* *Use with F Optics only	120-277V 347/480V	SP= 2.5KV Surge Protector

Part Number Example: PLEDSFCWP/22/5K/F/P/120-277/SP

Description: PowerLux LED Small Full Cutoff WallPack, 22W, 5000 Kelvin, Medium Beam Spread, Clear Prismatic Glass, 120-277V LED Electronic Driver, and 2.5KV Surge Protector

Catalog#		Type
Project		
Note		Date
Prepared by		

### APPLICATIONS

For parking areas, walkways, loading docks, tunnels, entrances, underpasses, recreation areas, area lighting, and urban lighting

### HOUSING FEATURES:

- Die cast aluminum housing & hinged full cutoff front frame
- 1/2" coin plugs with O-rings for conduit & photocell
- Textured architectural bronze powder coat finish over a chromate conversion coating
- Custom Colors Upon request: White, Black, Grey, etc.

### LENS:

Clear Flat Glass lens OR Clear Flat Prismatic Glass Lens

### Mounting:

Mount directly over a 4" outlet box, or use 1/2" surface conduit

### LED ARRAY FEATURES:

- Array lumens 2737 (C Optic); 2318 (F optic)
- Delivered lumens:  
C Optic: 2068  
F Optic: 2158
- CRI: 73 (C Optic); 80 (F Optic)
- CCT: 5000K
- Rated Life: 50,000 hours
- 5-Year warranty

### SYSTEM WATTAGE:

- Array 21.7W, System 25W

### LED DRIVER:

Dimmable Electronic Driver, 120-277V, 50/60Hz OR 347/480V, 50/60Hz  
Optional 2.5KV Surge Protector

### Listing & Rating

- CSA: Listed for wet locations
- DLC Listed as: **WPC12QF1X22U5KC**

**Assembled in the USA**

PowerLux® Corporation

**U.S. Manufacturer of Sustainable Energy Efficient Lighting Products**

1260 Liberty Way, Suite E Vista, CA 92081 Phone: 760-727-2360 Fax: 760-434-4766

Website: [www.powerlux.com](http://www.powerlux.com) E-mail: [klpowerlux@gmail.com](mailto:klpowerlux@gmail.com)

Based on prevailing model. Efficiency of ballast and efficacy of LED modules are ever improving. Please contact PowerLux® for latest updated information.

**PowerLux® Products Have Stood the Test of Time!**

151029  
Patents pending  
Specifications subject to change without prior notice  
© 2015 by PowerLux® Corporation. All rights reserved